

## Subdivision of frac. T. 27 N. R. 20 E.

## Chains

Land, mountainous and nearly level - grazing.  
Soil, stony and sandy, 3rd rate.

West on a true line bet. secs. 20 and 29.

Over nearly level land.

36.17 Intersect the Reservation bdy. 13.80 chs. S.  $14^{\circ} 56'$  E. of the  $90\frac{1}{2}$   
Mile Post.

Set an iron post 26 ins. in the ground, for C.C. of secs. 20 and 29,  
with brass cap stamped

PLIR in middle  
CC in E.  
T 27 N S 20 in NE. quadrant  
R 20 E S 29 in SE. quadrant  
2 notches on S. edge, and 4 on N. edge

Dig pits 24x18x12 ins. crosswise on each line, NW. and SE. of  
cor. 3 ft., and E. of cor. 7 ft. dist., and raise a mound of earth  
4 ft. base, 2 ft. high, E. of cor.

A closing cor. referring to surveys off the Reservation, which is a  
lime stone 14x10x6 ins., above ground, mkd. CC on W., PLIR on  
E., and witnessed by pits and md., hrs. S.  $14^{\circ} 56'$  E. 7.45 chs.  
dist.

Land, nearly level - grazing.  
Soil, sandy, 3rd rate.

From the cor. of secs. 20, 21, 28 and 29, I run

N.  $0^{\circ} 03'$  W. bet. secs. 20 and 21.

Over nearly level land.

40.00 Set an iron post 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor. bet. secs.  
20 and 21, with brass cap stamped

$\frac{1}{4}$  S 20 in W. half  
S 21 in E. half

Build a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

60.00 Begin ascent of low ridge.

75.50 Summit of low ridge, hrs. NW. and SE.

80.00 Set an iron post 26 ins. in the ground, for cor. of secs. 16, 17,  
20 and 21, with brass cap stamped

T 27 N S 16 in NE. quadrant  
R 20 E S 21 in SE. quadrant  
S 20 in SW. quadrant  
S 17 in NW. quadrant  
3 notches on S. and 4 on E. edges.