

## Subdivision of T. 28 N. R. 20 E.

## Chains.

a mound of earth  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

79.94 The cor. of secs. 19, 20, 29 and 30.

Land, gently rolling, grazing.  
Soil, sandy, 3rd rate.

From the cor. of secs. 19, 20, 29 and 30, I run

West on a true line bet. secs. 19 and 30.

Over gently rolling land.

34.90 Road, brs. N. and S.

40.00 Set an iron post 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor. bet. secs.  
19 and 30, with brass cap stamped

$\frac{1}{4}$  S 19 in N. half  
S 30 in S. half

Dig pits 18x18x12 ins. E. and W. of cor. 3 ft. dist., and raise  
a mound of earth  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

76.01 Intersect the W. bdy. of Tp. 8.89 chs. S.  $0^{\circ} 02'$  E. of the cor. of  
secs. 24 and 25, T. 28 N. R. 19 E.

Set an iron post 26 ins. in the ground, for C.C. of secs. 19 and 30,  
with brass cap stamped

C C in E.  
T 28 N S 19 in NE. quadrant  
R 20 E S 30 in SE. quadrant  
2 notches on S. and 4 notches on N. edge

Build a mound of stone, 4 ft. base, 2 ft. high, E. of cor.

Land, gently rolling, grazing.  
Soil, sandy, 3rd rate.

From the cor. of secs. 19, 20, 29 and 30, I run

N.  $0^{\circ} 04'$  W. bet. secs. 19 and 20.

Over gently rolling land.

30.50 Road, brs. E. and W.

40.00 Set an iron post 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor. bet. secs.  
19 and 20, with brass cap stamped

$\frac{1}{4}$  S 19 in W. half  
S 20 in E. half

Dig pits 18x18x12 ins. N. and S. of cor. 3 ft. dist., and raise  
a mound of earth  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.