Subdivision of T. 29 N. R. 20 E.

Chains.

Survey commenced Sept. 19, 1911, by Guy P. Harrington, U. S. Surveyor, and executed with Young & Sons Solar Transits, Nos.8388 & 8394 provided with two double verniers placed opposite each other on the horizontal limb, reading to single minutes of arc, which is also the least count of the verniers of the latitude and declination arcs.

For Polaris observation, see notes of T. 28 N. R. 20 E.

(For description of iron posts, see page 19.)

From the cor. of secs. 1, 2, 35 and 36, on S. bdy. of Tp., I run N. 0° 01' W. bet. secs. 35 and 36.

Ascending steep S. slope of ridge.

11.90 Top of ascent on ridge, brs. N. and W.

Thence steep descent of broken N. slope to desert.

40.00 Set an iron post 26 ins. in the ground, for ¼ sec. cor. bet. secs. 35 and 36, with brass cap stamped

¼ S 35 in W. half
S 36 in E. half

Build a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

50.00 Bottom of descent. Enter Smoke Creek Desert, brs. E. and W.

65.05 Road, brs. N. 40° W. and S. 30° E.

80.00 Set an iron post 26 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap stamped

T 29 N S 25 in NE. quadrant
R 20 E S 36 in SE. quadrant
S 35 in SW. quadrant
S 26 in NW. quadrant
1 notch on S. and E. edges.

Dig pits 18x18x12 ins. in each sec. 5½ ft. dist., and raise a mound of earth 4 ft. base, 2 ft. high, W. of cor.

Land, 55.00 chs. mountainous, barren. Balance, barren desert.
Soil, stony and sandy alkali, 3rd rate.

From the cor. of secs. 25, 26, 35 and 36, I run

East on a random line bet. secs. 25 and 36.

40.00 Set temp. ¼ sec. cor.

79.94 Falls 12 lks. S. of the cor. of secs. 25, 30, 31 and 36, on E. bdy. of Tp.

Thence I run