

Subdivision of frac. T. 24 N. R. 21 E.

Chains.

40.00 Set an iron post 26 ins. in the ground, for $\frac{1}{2}$ sec. cor. bet. secs. 21 and 28, with brass cap stamped

$\frac{1}{2}$ S 21 in N. half
S 28 in S. half

Build a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

52.00 Rocky spur, hrs. N. and S.

57.00 Rocky spur, hrs. N. and S.

80.00 Set an iron post 26 ins. in the ground, for the cor. of secs. 20, 21, 28 and 29, with brass cap stamped

T 24 N S 21 in NE. quadrant
R 21 E S 28 in SE. quadrant
S 29 in SW. quadrant
S 20 in NW. quadrant

2 notches on S. and 4 on E. edges.

Build a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, grazing mountainous.
Soil, stony, 3rd rate.

From the cor. of secs. 20, 21, 28 and 29, I run
S. $0^{\circ} 03'$ E. bet. secs. 28 and 29.

Ascending NE. slope of ridge.

5.50 Top of ridge, hrs. NW. and SE.

Thence along level summit.

13.00 Begin descent, of E. slope.

16.00 Draw, drains SE.

Thence along E. slope of mountain.

27.96 Intersect the Reservation bdy. 45 lks. S. $39^{\circ} 13'$ E. of $110\frac{1}{2}$ Mile Post.

Set an iron post 26 ins. in the ground, for closing cor. of secs. 28 and 29, with brass cap stamped

CC in N. edge
T 24 N S 28 in NE. quadrant
R 21 E S 29 in NW. quadrant
P L I R in middle
4 notches on E. edge and 2 on W. edge

Build a mound of stone, 4 ft. base, 12 ft. high, N. of cor.

Land, grazing mountainous and broken.
Soil, stony, 3rd rate.