Chains

40.00 Set an iron post 26 ins. in the ground, for } sec. cor. bet. secs.
27 and 28, with brass cap stamped

1 S 28 in W. helf S 27 in E. helf

Build a mound of stone, 2 ft. base, ly ft. high, W. of cor.

51.53 Intersect the Reservation bdy. 3.70 chs. S. 56° 58° E. of the 120 Mile Post.

Set an iron post 26 ins. in the ground, for closing cor. of secs. 27 and 28, with brass cap stamped

C C in N. edge T 23 N S 27 in NE. quadrant R 22 E S 28 in NW. quadrant P L I R in middle 3 notches on E. and W. edges.

Build a mound of stone, 4 ft. base, 2 ft. high, N. of cor.

The C.C. of secs. 27 and 28, referring to surveys off of the Reservation, brs. 5. 57° E., 2.25 chs. dist. This cor. is a granite stone 6x6x6 ins. above ground, mkd. C C on S. and witnessed by a mound of stone to South.

Land, grazing mountainous. Soil, rocky, 3rd rate.

From the cor. of secs. 21, 22, 27 and 28, I rum N. 0° 02' W. bet. secs. 21 and 22.

Over nearly level land.

2.00 Mountain Creek, 10 lks. wide, course N. 70° W.

Thence ascend low spur.

15.00 Top of spur, brs. NE. and SW.

Thence descend NW. slope.

25.00 Small mountain stream, 10 lks. wide, course N. 20° E.

Thence over rolling land.

40.00 Set an iron post 26 ins. in the ground, for \$\frac{1}{4}\$ sec. cor. bet. secs.

21 and 22, with brass cap stamped

\$ S 21 in W. half S 22 in E. half

Build a mound of stone, 2 ft. base, 12 ft. high, W. of cor.

80.00 Set an iron post 26 ins. in the ground, for cor. of secs. 15, 16, 21 and 22, with brass cap stamped