

Subdivision of frac. T. 24 N., R. 23 E.

Chains

Thence I run

N. 0° 03' E. bet. secs. 34 and 35.

Over rolling land, ascending sand hill.

30.00 Top of ascent. Ridge, brs. NW. and SE. Thence rolling.

40.00 Set an iron post for the 1/4 sec. cor. bet. secs. 34 and 35, with brass cap stamped

1/4 S 34 in W. half
S 35 in E. half
1912 in S.

Dig pits 18x18x12 ins. N. and S. of post, 3 ft. dist., and raise a mound of earth 3 1/2 ft. base, 1 1/2 ft. high, W. of cor.

80.00 Set an iron post for the cor. of secs. 26, 27, 34 and 35, with brass cap stamped

T 24 N S 26 in NE. quadrant
R 23 E S 35 in SE. quadrant
S 34 in SW. quadrant
S 27 in NW. quadrant
1912 in S.

1 notch on S. and 2 notches on E. edge

Dig pits 18x18x12 ins. in each sec. 5 1/2 ft. dist., and raise a mound of earth 4 ft. base, 2 ft. high, W. of cor.

Land, rolling, - grazing.
Soil, sandy, 3rd rate.
Scattered sage brush, full distance.

East on a true line bet. secs. 26 and 35.

Over rolling land.

3.80 Road, brs. N. and S.

22.16 Intersect the E. bdy. of Pyramid Lake Indian Reservation at a point from which the 24 1/2 M.P. brs. S. 19° 42' E., 12.52 chs.

Set an iron post for C.C. of secs. 26 and 35, with brass cap stamped

C C P L I R in W.
T 24 N S 35 in SW. quadrant
R 23 E S 26 in NW. quadrant
P L in E.
1912 in S.
5 notches on N. and 1 on S. edge