

Subdivision of frac. T. 24 N., R. 23 E.

Chains

with brass cap stamped

$\frac{1}{2}$ S 15 in N. half
S 22 1912 in S. half

Dig pits 18x18x12 ins. E. and W. of post, 3 ft. dist., and raise a mound of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

44.98 Intersect the E. bdy. of the Pyramid Lake Indian Reservation at a point from which the 28 Mile Post brs. N. $19^{\circ} 34'$ W., 17.94 chs.

Set an iron post for C.C. of secs. 15 and 22, with brass cap stamped

P L in E.
C O P L I R in W.
T 24 N S 22 in SW. quadrant
R 23 E S 15 in NW. quadrant
1912 in S.
3 notches on N. and S. edge

Build a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, rolling, - grazing.
Soil, stony, 3rd rate.
No timber.

From the cor. of secs. 15, 16, 21 and 22, I run N. $0^{\circ} 02'$ E. bet. secs. 15 and 16.

Over rolling land, ascending.

2.40 Top of ascent. Ridge, brs. E. and W. Thence along E. slope of ridge.

28.30 Dry drain, course N. 80° E.

40.00 Set an iron post for the $\frac{1}{2}$ sec. cor. bet. secs. 15 and 16, with brass cap stamped

$\frac{1}{2}$ S 16 in W. half
S 15 in E. half
1912 in S.

Build a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

62.90 Dry drain, course E.

77.20 Dry drain, course E.

80.00 Set an iron post for the cor. of secs. 9, 10, 15 and 16, with brass cap stamped