

Subdivision of frac. T. 24 N., R. 23 E.

Chains

- 40.00 Set an iron post for $\frac{1}{4}$ sec. cor. bet. secs. 18 and 19,
with brass cap stamped
- $\frac{1}{4}$ S 18 in N. half
S 19 1912 in S. half
- Build a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
- 59.05 Bottom of descent. Drain, course S. 10° E.
Thence over rolling land.
- 67.60 Drain, course S. 25° W.
- 80.00 Set an iron post for the cor. of secs. 13, 18, 19 and 24,
on W. bdy. of Tp., with brass cap stamped
- T 24 N S 18 in NE. quadrant
R 23 E S 19 in SE. quadrant
S 24 in SW. quadrant
R 22 E S 13 in NW. quadrant
1912 in S.
3 notches on N. and S. edges
- Build a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
- East Peak on Anaho Island, brs. N. $80^{\circ} 29'$ W.
- Land, rolling and mountainous, - grazing and barren.
Soil, stony, 3rd rate.
No timber.
-
- From the cor. of secs. 17, 18, 19 and 20, I run
N. $0^{\circ} 01'$ E. bet. secs. 17 and 18.
Over mountainous land, along W. slope of mountain, ascending.
- 13.90 Top of ascent. Ridge, brs. N. 15° E. and S. 15° W.
Thence over rough, broken land, along W. slope.
- 22.00 Draw, course W.
- 32.10 Draw, course S. 80° W.
- 38.30 Ridge, brs. E. and W.
- 40.00 Set an iron post for $\frac{1}{4}$ sec. cor. bet. secs. 17 and 18,
with brass cap stamped
- $\frac{1}{4}$ S 18 in W. half
S 17 in E. half
1912 in S.
- Build a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
- 42.70 Drain, course S. 75° W.