

Subdivision of T. 20 N. R. 24 E.

Chains

22.00 Lateral ditch, brs. N. 30° E. and S. 30° W.

Leave swamp, enter field.

23.00 Lateral ditch, brs. N. 45° E. and S. 45° W.

34.00 Lateral ditch, brs. N. 45° E. and S. 45° W.

38.00 Wire fence, brs. N. 40° E. and S. 40° W.

40.24 The cor. of secs. 3, 4, 9 and 10.

West of and alongside the stone, set an iron post, 3 ft.

long, 1 in. dia., 26 ins. in the ground, for witness

cor., with brass cap stamped

T 20 N S 3 in NE. quadrant

R 24 E S 10 in SE. quadrant

S 9 in SW. quadrant

S 4 in NW. quadrant

and W C in addition

5 notches on S. and 3 notches on E. edge

Land, level, irrigable.

Soil, river bottom, 1st rate.

From the cor. of secs. 3, 4, 9 and 10, I run

East on a random line bet. secs. 3 and 10.

20.00 Set temp. 1/16 sec. cor.

31.28 Falls 10 lks. S. of the C.C. of secs. 3 and 10, on reservation bdy., which is a volcanic rock, 14x10x6 ins. above ground, mkd. C C P L I R on W., S 10 on S., S 3 on N., and witnessed by pits and mound.

Returning to the cor. of secs. 3, 4, 9 and 10, thence

I run

N. 89° 50' E. on a true line bet. secs. 3 and 10.

2.00 Road, brs. N. 45° E. and S. 45° W.

19.91 At proportional dist., set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for 1/16 sec. cor. No. 2, bet. secs. 3 and 10 (W. 1/2) with brass cap stamped

1/16 S 3 in N. half

No 2 S 10 in S. half

Dig pits 18x18x12 ins. E. and W. of cor. 3 ft. dist.,

and raise a mound of earth 3 1/2 ft. base, 1 1/2 ft. high,

N. of cor.