

9th Standard Parallel North
Through Range 50 E.

Chains

By 1st set 39.96 chs.

By 2nd set 40.04 chs., mean of which is

40.00 Set an iron post, 3 ft. long, 1 in. in dia., with brass cap, 26 ins. in the ground for standard $\frac{1}{2}$ sec. cor. mkd.

S C $\frac{1}{2}$ S 35 in N. half
1911 in S. half
D V I R in N.

Build a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
N. of cor.

41.78 Top of ascent, Brs. NE. and SW.

Over nearly level table land.

54.78 Drain, course S. 10° W.

Difference in measurements of 80.00 chs. by two sets of chainmen is 16 lks., position of middle point

By 1st set 79.92 chs.

By 2nd set 80.08 chs., mean of which is

80.00 Set an iron post, 3 ft. long, 1 in. in dia., with brass cap, 26 ins. in the ground for S.C. of secs. 35 and 36, marked on top

T 46 N S 36 in NE. quadrant
R 50 E S 35 in NW. quadrant
S C on N. edge and 1911 on S.
D V I R in N.

5 notches on W. and 1 notch on E. edge
Build a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
N. of cor.

Land, broken plateau. Sage brush, 80.00 chs.
Soil, 3rd rate, stony.
No timber.

East on S. bdy. of sec. 36.

Over sage brush plateau.

4.78 Begin descent, SE. slope.

6.77 Foot of descent, brs. NE. and SW.

Across gently rolling bottom.

9.78 Dry channel of Sheep Creek, course SW., 2 chs. wide,
banks 4 ft. high, gradually ascend.

Difference in measurements of 40.00 chs. by two sets of chainmen is 2 lks., position of middle point