

East Boundary of T. 46 N., R. 51 E.

Chains

and raise a mound of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high,
W. of cor.

77.00 Owyhee-Whiterock wagon road, brs. NE. and S. 80° W.

80.00 Set an iron post for the cor. of secs. 1, 6, 7 and 12,
stamped in cap

T 46 N S 6 in NE. quadrant

R 52 E S 7 in SE. quadrant

S 12 in SW. quadrant

R 51 E S 1 in NW. quadrant

1911 in S.

5 notches on S. and 1 notch on N. edge

Dig pits $18 \times 18 \times 12$ ins. in each sec. $5\frac{1}{2}$ ft. dist., and
raise a mound of earth 4 ft. base, 2 ft. high, W. of
cor.

Land, rolling. (Grazing land, 80.00 chs.)

Soil, gravelly, 2nd rate.

No timber.

Sage brush, 80.00 chs.

North bet. secs. 1 and 6.

Over rolling land, through sage brush.

40.00 Set an iron post for the $\frac{1}{4}$ sec. cor. bet. secs. 1 and 6,
stamped in cap

$\frac{1}{4}$ S 1 in W. half

S 6 in E. half

1911 in S.

Dig pits $18 \times 18 \times 12$ ins. N. and S. of post 3 ft. dist.,
and raise a mound of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high,
W. of cor.

80.00 Set an iron post for cor. of Tps. 46 and 47 N., Rgs. 51
and 52 E., stamped in cap

T 47 N S 31 in NE. quadrant

R 52 E S 6 in SE. quadrant

T 46 N S 1 in SW. quadrant

R 51 E S 36 in NW. quadrant

1911 in S.

6 notches on E., S., W. and N. edge

Dig pits $24 \times 24 \times 12$ ins. on each line, N., E. and W., 4
ft., and S. of post 8 ft. dist.; and raise a mound of
earth 5 ft. base, $2\frac{1}{2}$ ft. high, S. of cor.

Land, rolling. (Grazing land, 80.00 chs.)

Soil, gravelly, 2nd rate.

No timber.

Sage brush, 80.00 chs.

July 15, 1911.