

North Boundary of T. 46 N., R. 50 E.

Chains

stamped in cap

T 47 N S 34 in NE. quadrant
 R 50 E S 3 in SE. quadrant
 T 46 N S 4 in SW. quadrant
 S 33 in NW. quadrant
 1911 in S.
 3 notches on E. and W. edges.

Dig pits 18x18x12 ins. in each sec. 5 1/2 ft. dist.; and
 raise a mound of earth 4 ft. base, 2 ft. high, W. of
 cor.

Land, high and rolling. (Grazing, sage brush land.)
 Soil, stony and gravelly, 3rd rate.
 No timber.

 West on a true line bet. secs. 4 and 33.

Through sage brush, gradually descending.

20.00 Foot of descent; begin ascent of SE. slope.

The true point for the 1/4 sec. cor. falls in broken rim
 rock, therefore at

38.66 Set an iron post for W.C. to the 1/4 sec. cor. bet. secs. 4
 and 33, stamped in cap

W C 1/4 S 33 in N. half
 S 4 1911 in S. half

Build a mound of stone 2 ft. base, 1 1/2 ft. high, N. of cor.

40.00 True point for 1/4 sec. cor. bet. secs. 4 and 33.

Top of ascent; begin gradual descent to

59.10 Intersect the W. bdy. of the Duck Valley Indian Reservation
 at a point from which the SW. cor. of the reservation,
 on the 9th Standard Parallel N., hrs. South 480.02 chs.
 dist.

Set an iron post for C.C. of Tps. 46 and 47 N., R. 50 E.,
 stamped in cap

T 47 N S 33 in NE.
 T 46 N S 4 in SE.
 R 50 E C C D V I R in E.
 1911 in S.
 6 notches on N. and S. edges

Build a mound of stone 3 ft. base, 2 ft. high, E. of
 cor.

Land, high and rolling. (Grazing land, 59.10 chs.)
 Soil, stony, 3rd rate.
 No timber.

stop

Sept. 14, 1911.