

Subdivision of T. 46 N., R. 50 E.

Chains

Descending rocky NW. slope.

21.00 Foot of descent; thence over rolling land.

40.00 Set an iron post for the 1/4 sec. cor. bet. secs. 28 and 33, stamped in cap

1/4 S 28 in N. half  
S 33 1911 in S. half

Build a mound of stone 2 ft. base, 1 1/2 ft. high, N. of cor.

50.25 Descend steep rocky NW. slope.

54.00 Bottom of canyon, course SW. Spring branch, 4 lks. wide, course SW.

54.50 Begin ascent of SE. slope out of canyon.

58.10 Top of ascent; thence over rolling, rocky land.

59.28 Intersect the W. bdy. of the Duck Valley Indian Reservation at a point from which the SW. cor. of the Duck Valley Indian Reservation, on the 9th Standard Parallel N., previously described, bears South, 80.00 chs. dist. Set an iron post for the C.C. of secs. 28 and 33, stamped in cap

T 46 N S 28 in NE. quadrant  
R 50 E S 33 in SE. quadrant  
D V I R C C in E.  
1911 in S.  
1 notch on S. and 5 notches on N. edge

Build a mound of stone 3 ft. base, 2 ft. high, E. of cor.

Land, mountainous. (Grazing land, 59.28 chs.)  
Soil, stony, 4th rate.  
Sage brush, 59.28 chs.  
No timber.

-----  
N. 0° 02' W. bet. secs. 27 and 28.

Descending barren N. slope.

8.00 Patch of slide rock, 2 chs. across.

16.00 Foot of descent. Thence over rolling land, through sage brush.

40.00 Set an iron post for the 1/4 sec. cor. bet. secs. 27 and 28, stamped in cap

1/4 S 28 in W. half  
S 27 in E. half  
1911 in S.