

Subdivision of T. 46 N., R. 50 E.

Chains

59.13 Intersect the W. bdy. of the Duck Valley Indian Reservation at a point from which the C.C. of secs. 16 and 21, brs. South, 79.90 chs. dist.

Set an iron post for C.C. of secs. 9 and 16, stamped in cap

T 46 N S 9 in NE. quadrant  
R 50 E S 16 in SE. quadrant  
D V I R C C in E.  
1911 in S.

4 notches on S. and 2 notches on N. edge

Build a mound of stone 3 ft. base, 2 ft. high, E. of cor.

Land, heavily rolling and mountainous. (Grazing land).  
Soil, stony, 3rd rate.  
Sage brush, 59.13 chs.  
No timber.

-----  
From the cor. of secs. 9, 10, 15 and 16, I run  
N. 0° 02' W. bet. secs. 9 and 10.

Along W. slope.

16.00 Begin descent of NW. slope.

38.11 Drain, course W. Ascend S. slope.

39.60 Dim road, brs. E. and W.

40.00 Set an iron post for the 1/4 sec. cor. bet. secs. 9 and 10,  
stamped in cap

1/4 S 9 in W. half  
S 10 in E. half  
1911 in S.

Build a mound of stone 2 ft. base, 1 1/2 ft. high, W. of cor.

40.20 Top of ascent. Thence descend gradual N. slope.

42.00 Foot of descent. Thence ascend gradual S. slope.

57.00 Patch of rocks about 2 chs. sq.

70.00 Top of ascent. Thence descend rocky N. slope.

80.00 Set an iron post for the cor. of secs. 3, 4, 9 and 10,  
stamped in cap

T 46 N S 3 in NE. quadrant  
R 50 E S 10 in SE. quadrant  
S 9 in SW. quadrant  
S 4 in NW. quadrant  
1911 in S.

5 notches on S. and 3 notches on E. edges

Build a mound of stone 2 ft. base, 1 1/2 ft. high, W. of cor.