

Subdivision of T. 47 N., R. 52 E.

Chains

The iron posts used in this survey are 3 feet long, 1 inch in diameter, and are set 26 ins. in the ground. The posts are filled with cement and fitted with brass caps.

The SE<sup>a</sup> cor. of this Tp. is in Lat. 41° 55' 31" N.; Long. 116° 05' 05" W.

Aug. 21, 1911. At 8 A.M., l.m.t., I set off 41° 56' on the lat. arc, 12° 23' N. on the decl. arc, and determine a meridian with the solar at the cor. of secs. 1, 2, 35 and 36, on S. bdy. of Tp., previously described.

Thence I run

N. 0° 01' W. bet. secs. 35 and 36.

Over level prairie.

- .50 Leave prairie, enter dense willow brush, brs. E. and W.
- 3.80 To Owyhee River, 60 lks. wide, banks 6 ft. high, course W., soon turns N.
- 8.00 Bend in Owyhee River, course from S. 10° W. to W., general course NW.
- 14.00 Owyhee - Mountain City wagon road, brs. NW. and SE.  
Leave willow brush and enter sage brush, brs. NW. and SE.  
Thence gradual ascent.
- 20.00 Set an iron post for the 1/16 sec. cor. No. 12, bet. secs. 35 and 36 (S $\frac{1}{2}$ ), stamped in cap  
  - 1/16 S 35 in W. half
  - S 36 in E. half
  - No 12 1911 in S.

Build a mound of stone 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.
- 29.70 Telephone line, brs. N. 10° W. and S. 10° E.
- 40.00 Set an iron post for the  $\frac{1}{4}$  sec. cor. bet. secs. 35 and 36, stamped in cap  
  - $\frac{1}{4}$  S 35 in W. half
  - S 36 in E. half
  - 1911 in S.

Build a mound of stone 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.
- 60.00 Set an iron post for the 1/16 sec. cor. No. 6, bet. secs. 35 and 36 (N $\frac{1}{2}$ ), stamped in cap  
  - 1/16 S 35 in W. half
  - S 36 in E. half
  - No 6 1911 in S.