245

Chains

Leave brush.

20.76 Set an iron post for 1/16 sec. cor. No. 6 bet. secs. 1 and 6, N2, with brass cap stamped

1/16 S l in W. S 6 " E. No 6 1912 in S.

Dig pits 18x18x12 ins. N. and S. of post 3 ft. dist.; and raise mound of earth $3\frac{1}{2}$ ft.base, $1\frac{1}{2}$ ft.high, W. of cor.

24.30 Irrigation canal, 10 lks. wide, course N. 65° E.

31.00 Begin steep ascent of bluff, brs. E. and W.

37.60 Top of ascent, brs. E. and W.

Thence over broken land.

39.50 Draw, drains S. 45° E.

41.52 The \(\frac{1}{4}\) sec. cor. bet. secs. 1 and 6, W. of and alongside which I set an iron post for W. C., with brass cap stamped

1 S l in W. S 6 " E. W C 1912 in S.

Thence I run

South on a random line bet. secs. 1 and 6, S_2^1 .

5.41 No trace of C. C. on Res'n bdy. Set temp. cor.

41.37 Fall 14½ lks. W. of cor. of secs. 1, 6, 7 and 12, which is a granite stone 12x10x8 ins., firmly set, marked 5 notches on the S. and 1 on the N., and witnessed by a mound of stone 4 ft. base, 2 ft. high, to the W. This mound was probably rebuilt by Barber, but he states in his notes that he identified the original corner, so I accept this position for cor.

Returning to the \(\frac{1}{4} \) sec. cor. bet. secs. 1 and 6,

Thence I run

S. 0° 12' E. on a true line bet. secs. 1 and 6, S_2^1 , Over broken land.

1.48 Ridge brs. E. and W.

5.60 At proportional distance of S. half of mile, I set an iron post for C. C. of secs. 1 and 6 on Res'n bdy.,