

M. D. 16

11  
51

West, on true line between Secs. 6<sup>th</sup> and 31  
Var. 16° 30' E

40.00 Set a Granite Stone 16 x 10 x 8 in, 11<sup>u</sup>/<sub>16</sub> in  
ground, in stone mound, with pits  
24 x 18 x 12 in, marked 1/4 for 1/4 Sec. 6<sup>th</sup>

77.60 Set a Granite Stone 20 x 12 x 10 in, 14<sup>u</sup>/<sub>16</sub> in  
ground, in stone mound, with pits  
24 x 18 x 12 in, marked 6 notches on the  
N. S., E<sup>th</sup> and W. sides for Corner to  
Townships 24<sup>th</sup> and 25<sup>th</sup> North, Ranges  
41<sup>st</sup> and 42<sup>nd</sup> East.  
Sand hilly - Soil 3<sup>rd</sup> rate, rocky  
Greasewood.

March 28<sup>th</sup> 1876

From the Corner to T<sup>h</sup> 24<sup>th</sup> and 25<sup>th</sup> N  
R<sup>th</sup> 41<sup>st</sup> and 42<sup>nd</sup> E, Iron between  
said Ranges

North, between Sections 31<sup>st</sup> and 36<sup>th</sup>

Var. 16° 30' E.

Over rolling hills, Descending gradually