210. 210 73. T21S., R. 56 E., Mt. D. M.

	North on a true line between sections 1-6	·
	Descend.	*
3.00	Cross Gulch, or lks. wide, Course Hest and ascend,	
21.50	Top of Spur, bears I. N. E. and descend.	
38.50	Cross Gulch, 10 lks. wide, Course f. H. and ascend.	
40.00	Set $Sand$ Stone $16/x / 0 x 8$, in Stone mound,	
	4 ft. in diameter at base, by 2 ft. in height, for \frac{1}{2} sec. cor.	
47.00	Top of Ridge, bears & A. and descend.	
78.44	Intersect 3 d. Standard line. South 1.73 chs.	4
	Hest of Standard cor. to Sees. 205. Rs. 56-5 7 & and	
	Set Post, 4 in. square, 1 ft. in earth, 1 ft. above Stone	
	mound, 4½ ft. in diameter at base, by 2 ft. in height, for	
	closing The Cor. to Tps. 2/8. Rs. 56 & 57 R.	
	from which bears, a	
	Pine /0 in. dia. I. 63/4 6, 39/ Uks. dist.	
	An Oak 4 in. dia. S. 24/4° N. 133 Ws. dist.	,
	Land mountainous	_
	Soii 3vd rate.	
	Timber and undergrowth of Poni Oak	× ·
	Saybrush. W. H. Proctor, Apr. 1. 1881.	