

S. B. T. 4 S., R. 3 E., Mt. D. M.

West on a true line on S. B. of Section 31.

Va. $16^{\circ} 40'$ East.

Ascend.

- 3.00 ↪ Top of Spur, bears N. & S. and descend.
- 8.92 Cross Gulch, 30 lks. wide, Course N. 15° E. and ascend.
- 30.00 ↪ Top of Spur, bears N. 75° E. & S. 75° W. and descend.
- 40.00 ↪ Set Sand Stone $20 \times 12 \times 8$, in Stone mound, 4 ft. in diameter at base, by 2 ft. in height, for $\frac{1}{4}$ sec. cor.
- 41.09 Cross Gulch, 6 lks. wide, Course N. 10° W. and ascend.
- 47.00 ↪ Top of Spur, bears N. & S. and descend.
- 64.00 ↪ Cross Canon, 10 lks. wide, Course N. 15° E. and ascend.
- 72.00 ↪ Top of Spur, bears N. 15° E. & S. 15° W. and descend.
- 80.00 ↪ Set Sand Stone $14 \times 10 \times 10$, in Stone mound $4\frac{1}{2}$ ft. in diameter at base, by 2 ft. in height, for cor.

Standard

The Cor. to Tps. 4 S. Rs. 52 & 53 E.

Land mountainous.

Soil 2d. & 3d. rate;

Undergrowth Sagebrush.

J. A. Magee Mar. 22, 1881.

M. F. Reilly Apr. 30, 1881.