

103
3²⁹ Standard Parallel along.

107

S. B. T. 12 S., R. 68 E., Mt. D. M.

Chains.

Closing
From the Cor. to Tps. 13 S. Rs. 67 & 68 E.
I run,

East on a true line
Va. 15° 58' East

26.64

Set a Sand stone 24 x 19 x 15 ins. 18 ins. in the ground, for Standard Cor. to Tps. 12 S., R's 67 and 68 E., marked S. C. with 6 notches on N. & W. edges, and raised a mound of stone, Pits impracticable.

From which corner I run.

East. on a true line on S. B. of Section 31
Va. 15° 58' East.

40.00

Set a Sand stone 20 x 10 x 8 ins., 15 ins. in the ground, for ^{Standard} 1/2 Sec. Cor., marked S. C. 1/2 on N. face, dug pits, 18 x 18 x 12 ins., N. and S. of stone 5 1/2 ft. dist., and raised a mound of earth 1 1/2 ft. high, 3 1/2 ft. base.

80.00

Set a Sand stone 17 x 7 x 5 ins. 12 ins. in the ground for Standard Cor. to Secs. 31 and 32 marked S. C., with 5 notches on E. and 1 notch on W. edges, dug pits 18 x 18 x 12 ins. N., E. and W. of stone, 5 1/2 ft. dist., and raised a mound of earth 2 ft. high 4 1/2 ft. base.