

14

5th Standard Parallel along.

S. B., T. 26 N., R. 60 E., Mt. D. M.

Chains.

East. on a true line on S. B. of Section 36,

Va. 16° 30' East.

Ascend.

5.00 Enter timber.

30.00 Top of Spur, bears N. & S. and descend.

40.00 Set a *lime* stone 36 x 36 x 8 ins., 37
 ins. in the ground, for Standard $\frac{1}{2}$ Sec. Cor., marked S.
 C. $\frac{1}{4}$ on N. face, dug pits, 18 x 18 x 12 ins., N. and S.
 of stone 5 $\frac{1}{2}$ ft. dist., and raised a mound of earth 1 $\frac{1}{2}$ ft.
 high, 3 $\frac{1}{2}$ ft. base. *from which*
 A Juniper 10 ins. diam. bears N. 17° E. 36 kls. dist.
 marked $\frac{1}{2}$ S. B. T.

80.00 Set a post, 4 $\frac{1}{2}$ ft. long, 4 ins. square, 24 ins. in the
 ground, for Standard Cor. to Tps 26 N., R's 60 and
 61 E. marked ^{S. C.} T. 26 N. on N. R. 61 E. S. 31,
 on E. and R. 60 E. S. 36 on W. faces, with
 6 notches on N. E. & W. faces; *from which*
 A Cedar 14 ins. diam. bears N. 33° E. 36 kls. dist.
 marked T. 26 N., R. 61 E., S., 31 B. T.

A Cedar 12 ins. diam. bears N. 18° W. 90 kls. dist.
 marked T. 26 N., R. 60 E., S., 36 B. T.