

5<sup>th</sup> Standard Parallel along.

S. B., T. 26 N., R. 63 E., Mt. D. M.

## Chains.

Pine 18 ins diam bears N.  $18\frac{1}{4}^{\circ}$  E. 54 lks. dist.  
marked T. 264 R. 63 E., S., 32 B. T.

A Pine 10 ins diam bears N.  $74\frac{1}{2}^{\circ}$  W. 31 lks. dist.  
marked T. 264 R. 63 E., S., 31 B. T.

Mahogany 8 ins diam bears N.  $39^{\circ}$  E. 12 lks. dist.  
marked T. 264 R. 63 E., S., 32 B. T.

Land mountainous

Soil 3d. rate.

Timber and undergrowth of Mahogany,  
Cottonwood and Bunchgrass.

East. on a true line on S. B. of Section 32.

Va.  $16^{\circ} 30'$  East.

Ascend.

21.00

Top of Ridge, bears N. W. &amp; S. E. and descend.

39.00

Cross Gulch, 5 lks. wide, Course N. W. and ascend.

40.00

Set a lime stone  $38 \times 13 \times 8$  ins., 21  
ins. in the ground, for Standard  $\frac{1}{4}$  Sec. Cor., marked S.  
C.  $\frac{1}{4}$  on N. face, and raised a mound of stone. Pits  
impracticable.

from which