

6th Standard Parallel along.

S. B., T. 26th N., R. 68 E., Mt. D. M.

Chains.

East. on a true line on S. B. of Section 36.

Va. 17° East.

Ascend.

15.00

Top of Ridge, bears N. & S. and descend.

29.00

Cross Gulch, 6 lks. wide, Course South and ascend.

40.00

Set a line stone 38 x 4 x 6 ins., 37 ins. in the ground, for Standard $\frac{1}{2}$ Sec. Cor., marked S.

C. $\frac{1}{4}$ on N. face, and raised a mound of stone. Pits impracticable.

A Pine 13 in dia. m bears N. 70 E. 54 lks. dist. marked $\frac{1}{2}$ S. B. T. from which

A Pine 9 in dia. m bears N. 43 N. 80 lks. dist. marked $\frac{1}{2}$ S. B. T.

50.00

Top of Ridge, bears N. N. & S. E. and descend.

80.00

Set a post, 4 ft. long, 4 ins. square, 12 ins. in the

ground, for Standard Cor. to Tps. 31 N. R. 68 & 69 E. marked S. C. T. 31 N. R. 68 E. S. 36 on N.

R. 68 S. Show N. faces, with 6 notches on and notch on . faces, and raised a mound of stone

2 ft. high, 4 $\frac{1}{2}$ ft. base around post. Pits impracticable.

from which

A Pine 13 in dia. m bears N. 68 $\frac{1}{2}$ E. 110 lks. dist. marked T. 26 N. R. 68 E. S. 36 B. T.