

N. B., T. 27 N., R. 69 E., Mt. D. M.

Chains.

North on a true line between sections 31 + 36

Va. 17° East.

Descend.

13.00 Cross Gulch, 6 lks. wide, Course S. W. and ascend.

30.00 Top of Ridge, bears E. & N. and descend.

40.00 Set a line stone 38 x 14 x 6 ins., 3½ ins. in the ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N. face, and raised a mound of stone. Pits impracticable.

from which

Cedar 10 in diam bears N. 18° E 20 lks. dist. marked $\frac{1}{4}$ S. B. T.

43.00 Cross Gulch, 6 lks. wide, Course N. W. and ascend.

60.00 Top of Ridge, bears N. W. & S. E. and descend.

80.00 Set a post 4 ft. long, 4 ins. square, 12 ins. in the ground, for Cor. to Secs. 31 - 31 - 35 - 36 marked T. 27 N. S. 30, on N. E., R. 69 E., S. 31 on S. E., S. 36 on S. W. and S. 35 on N. W. face, with $\frac{1}{4}$ notch on S. and $\frac{1}{2}$ notch on E. edges; dug pits, 18 x 18 x 12 ins. in each Sec., $5\frac{1}{2}$ ft. dist., and raised a mound of earth 2 ft. high, $4\frac{1}{2}$ ft. base around post.

from which