

N. B., T. 26 N., R. 68 E., Mt. D. M.

Chains.

North on a true line between sections 1-6.

Va. $16^{\circ} 30'$ East.

Ascend.

18.00 Top of Ridge, bears N. W. & S. E. and descend.
 36.00 Cross Gulch, 4 lks. wide, Course N. W. and ascend.
 40.00 Set a line stone $34 \times 12 \times 8$ ins., 18
 ins. in the ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N.
 face, and raised a mound of stone. Pits

impracticable.

from which

A Juniper 12 in diam. bears S. 30° E. 65 lks. dist.
 marked $\frac{1}{4}$ S. B. T.

A Juniper 14 in diam. bears S. $24\frac{1}{2}^{\circ}$ W. 50 lks. dist.
 marked $\frac{1}{4}$ S. B. T.

48.00 Top of Ridge, bears N. W. & S. E. and descend.

65.00 Cross Gulch, 5 lks. wide, Course N. W. and ascend.

80.00 Set a line stone $38 \times 16 \times 8$ ins. 21 ins. in
 the ground, for Cor. to Tps. 26 and 27 N. R's 67 and
 68 E., marked with 6 notches on each edge, and raised a
 mound of stone. Pits impracticable. from which

A Pine 12 in diam. bears N. $16\frac{3}{4}^{\circ}$ E. 52 lks. dist.
 marked T. 27 N. R. 68 E., S., 31 B. T.