

144

419

N. B., T. 29 N., R. 66 E., Mt. D. M.

Chains.

North on a true line between sections

31 & 36

Va. 17° East.

Ascend.

10.00 Top of Ridge, bears N. 50° W. S. 50° E. and descend.

38.00 Cross Gulch, 5' lks. wide, Course N. 50° W. and ascend.

40.00 Set a *lime* stone $38 \times 10 \times 8$ ins., 31 ins. in the ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on $\frac{1}{16}$ face, and raised a mound of stone. Pits impracticable.

from which

A Pine $\frac{1}{8}$ ins. diam. bears S. 33° N. 62 lks. dist. marked $\frac{1}{4}$ S. B. T.A Pine $\frac{1}{6}$ ins. diam. bears S. $18\frac{3}{4}^{\circ}$ E. 70 lks. dist. marked $\frac{1}{4}$ S. B. T.

60.00 Top of Ridge, bears N. 50° W. S. 50° E. and descend.

80.00 Set a *lime* stone $26 \times 8 \times 6$ ins. / 8 ins. in the ground for Cor. to Secs. 30-31-35-36 marked with / notch on S. and 5 notched on N. edges and raised a mound of stone. Pits impracticable.

from which

A Mahogany 23 ins. diam. bears N. $68\frac{3}{4}^{\circ}$ E. 83 lks. dist. marked T. 29 N. R. 66 E. S. 30 B. T.