

360
Township

30 NORTH Range 60 EAST

44

Monte Diablo Base and Meridian.

Chains.

North, on a ~~line~~ line between Sections 4 and 5.

Variation

17°

East.

Over nearly level ground

40.00

Set a post 3 ft. long, 3 ins. diam. with marked stone, 12 ins. in the ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4} S.$ on W face, dug pits, 18 x 18 x 12 ins., W and $S.$ of post $5\frac{1}{2}$ ft. dist., and raised a mound of earth $1\frac{1}{2}$ ft. high, $3\frac{1}{2}$ ft. base, around post.

57.00

Cross Road, bears, NW & SE

78.61

Intersect the ~~Sixth~~ Standard Parallel North at a point 17.59 chs. W of the Standard Cor. to Secs. 31 and 33 T. 3 M.R. 59 E.Which is a post 4 ft. long, 4 ins. square, firmly set in the ground, marked $T. 31 N. R. 60 E. S. 60 N.$ $S. 33 N. E. and S. 31$ on $W.$ faces, with $\frac{1}{4}$ notches on $E.$ and $\frac{1}{2}$ notches on $W.$ edges. Pits 10.8^{ft} W of post and mound of earth around post at point of intersection.Set a Limestone 15 x 12 x 10 ins. 10 ins. in the ground for Closing Cor. to Secs. 4 and 5 marked C. with $\frac{1}{4}$ notches on $E.$ and $\frac{1}{2}$ notches on $W.$ edges, and raised a mound of earth alongside.August 2nd 1882From the corner to Section 31 E. 32 5^{sq.} 6. on the South BoundaryWhich is a post 4 ft. long, 4 ins. square, firmly set in the ground, marked T. 31 N. S. 33 on N. E., R. 60 E. S. 4 on S. E. R. 60 E. S. 5 on S. W. and S. 32 on N. W. faces, with $\frac{1}{4}$ notches on $E.$ and $\frac{1}{2}$ notches on $W.$ edges.and pits 18 x 18 x 12 ins. in each sec., $5\frac{1}{2}$ ft. dist., and mound of earth 2 ft. high, $4\frac{1}{2}$ ft. base around post.