

Chains North, on a *true* line between Sections 5 and 6. Variation 17 1/2° East.

1.00 Top of Ridge, bears *N 1/2 W 1/2 E* and descend along *N* slope of Ridge

40.00 Set a Porphyry stone 16 x 12 x 7 ins. 10 ins. in the ground, for 1/2 Sec. Cor., marked 1/2 on *N* face, and raised a mound of stone alongside. Ravine about 60 feet deep, course *N 12 chains W of line*

80.17 Intersect the *Fifth* Standard Parallel North at a point 3.21 chs. West of the Standard Cor. to Secs. 31 and 37 T. 25 N R. 36 E which is a stone 37 x 9 x 8 ins. 24 ins. in the ground marked with 5 notches on *E* and 1 notch on *N* edge and mound of stone

At Point of intersection *D*
 Set a *Trap* stone 16 x 12 x 10 ins. 10 ins. in the ground for Closing Cor. to Secs. 5 and 6 marked *C* with 5 notches on *E*. and 1 notch on *W*. edges, and raised a mound of stone alongside.

*Land Mountainous
 Excellent grass
 Soil rocky low 2nd rate*

I carefully examined the adjustments of my surveying apparatus to-day, particularly the latitude and reversing apparatus, and found them correct. Kirk W. Taylor

Sept 17/88