

E. B. T. 23 S., R. 6 E., Mt. D. M.

Chains.

Standard
From the Cor. to Tps. 32 S., Rs. 65 & 66 E.,
I run,

West. on a true line on S. B. of Section 36.

Va. 15° 00' East.

and at

20.41 Set a granite stone 24 x 18 x 16 ins. 18 ins. in the
ground, for Closing Cor. to Tps. 33 S., R's 65 and
66 E., marked C. (1. with 6 notches on S. & E. sides,
and raised a mound of stone, alongside.

Pits impracticable,

From which corner I run.

South on a true line between sections 1 and 6.

Va. 15° 00' East.

Descend.

40.00 Set a granite stone 14 x 10 x 9 ins., 9
ins. in the ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W.
face, dug pits, 18 x 18 x 12 ins., N. and S. of stone
5½ ft. dist., and raised a mound of earth 1½ ft. high,
3½ ft. base. alongside.

80.00 Set a granite stone 17 x 11 x 10 ins. 11 ins. in
the ground for Cor. to Secs. 1, 6, 7 and 12, marked
with 5 notch on S. and 1 notch on W. edges, dug pits
18 x 18 x 12 ins. in each Sec., 5½ ft. dist., and raised a
mound of earth 2 ft. high 4½ ft. base. alongside.