

Chains North, on a ^{true} ~~random~~ line between Sections 1 and 2. Variation 17 1/2° East.

Ascend through scattering timber

20.00 Top of Ridge, bears N 65° W and descend

31.00 Ravine about 100 feet deep, course N N W and ascend

40.00 Set a Granite stone 22 x 15 x 10 ins. 19 ins. in the ground, for 1/4 Sec. Cor., marked 1/4 on N face, and raised a mound of stone alongside. Pits impracticable.

46.50 Top of Ridge, bears N W + E and descend

57.50 Ravine about 125 feet deep, course N W and ascend

74.00 Top of Ridge, bears N 50° W and descend

80.12 Intersect the Fifth Standard Parallel North at a point 12.94 chs. West of the Standard Cor. to Secs. 35 and 36 T. 26 N R. 39 E which is a stone 18 x 12 x 10 ins. 12 ins. in the ground marked with 1 notch on E and 5 notch on W edges and mound of stone

At Point of intersection I

Set a granite stone 21 x 12 x 9 ins. 15 ins. in the ground for closing Cor. to Secs. 1 and 2 marked C with 1 notch on E. and 5 notch on W. edges, and raised a mound of stone alongside. covered with earth

Land mountainous scattering timber sage and grass Soil rocky and 3/4 rate.

Nov 9th 1882