

16

Township

21 NORTH

Range

60 EAST

Monte Diablo Base and Meridian.

Chains

From the corner to Sections 35, 36,

on the 4th Standard
 which is a stone 18 x 12 x 10 ins. ins. in the ground
 marked with 1 notch on S and 5 notches on W edges
 and mound of stone

I run

North on a true line between sections 35 & 36

Latitude $39^{\circ} 37' 28''$ Variation $17' 14''$ East.

along E slope of hill through scattering timber

40.00 Set a post 3 ft. long, 3 ins. diam. with marked stone,
 12 ins. in the ground, for $\frac{1}{2}$ Sec. Cor., marked $\frac{1}{2}$ S. on
 W face, dug pits, 18 x 18 x 12 ins., N and S of
 post $5\frac{1}{2}$ ft. dist., and raised a mound of earth $1\frac{1}{2}$ ft.
 high, $3\frac{1}{2}$ ft. base, around post.

48.00 Enter Valley hrs C & W and

Leave scattering timber

80.00 Set a granite stone 13 x 11 x 6 ins. 8 ins. in
 the ground for Cor. to Secs. 25, 26, 35 & 36 marked
 with 1 notch on S. and 1 notch on E. edges and
 dug pits, 18 x 18 x 12 ins. in each Sec., $5\frac{1}{2}$ ft. dist.,
 and raised a mound of earth 2 ft. high, $4\frac{1}{2}$ ft. base
 alongside

1st 48.00 chs. railing

but 32.00 " level

soil 2nd rate