

From the Cor. to Tps. 14 & 15 N. Rs. 36 & 37

I run East on random line on N. B. of Tp.
 170 East.

I set temporary corners at every half mile, and at 5
 miles 77.20 chs. I arrive at a point 60 lks. N of Cor. to

Tps. 14 & 15 N. Rs. 36 & 37. Which is
 a stone 15 x 11 x 10. Marked with
 6. Notches on each edge and mound
 of stone alongside - from which Cor.
 I run N 89° 56' W. a true line between sections 1 & 36
 Variation 170° - East.

Descend 8° slope

17.00 Ravine about 30 feet deep, course A and ascend 15° slope

26.00 Top of Ridge, bears NE & W and descend 6° slope

40.00 Set a Sand stone 6 x 12 x 10 ins. 11
 ins. in the ground, for 1/2 Sec. Cor., marked 1/2 on N
 face, and raised a mound of stone alongside. Pits impracticable.

61.00 Ravine about 20 feet deep, course N and ascend 7° slope

80.00 Set a Sand stone 8 x 12 x 10 ins. 1/2 ins. in
 the ground for Cor. to Secs. 1 - 2 - 35 & 36 marked
 with 6 notch 6 on N. and 1 notch - on E. edges and
 raised a mound of stone alongside. Pits impracticable.

No necessary correction corresponding to the
 given slopes. Timber as before and
 the corner located according to the
 true distance there obtained
 Land mountainous scattering timber
 sagebrush and bunchgrass soil 3 rate