THIRD STANDARD PARALLEL NORTH

THROUGH RANGE 34 EAST

West on S. boundary Sec. 31
Variation 17° East.

Descend 8° Slope
4.80 Bottom of Ravine about 80 ft. deep course N E
and ascend 6° slope along N.E slope of ridge

40.00 Set a Trachyte stone 16 x 12 x 7 ins. 11 ins. in the ground, for Standard ¼ Sec. Cor., marked SC ¼ on N face, ~~and raised a mound of stone alongside.~~
Pits impracticable.

45.00 Ascend 7° slope
60.00 Ascend 18° slope
67.00 Top of Ridge, bears N W & S E and descend 10° Slope to Cor

80.00 Set a Trap stone 18 x 10 x 10 ins. 12 ins. in the ground for Standard Cor. to T 16 N. Rs. 33 & 34 marked S C. with 6 notches on N E & — W. edges, and raised a mound of stone alongside. Pits impracticable.
The necessary corrections corresponding to the given slopes has been applied and the corner located according to the true distance thus obtained

Land mountainous scattering timber
sagebrush and bunchgrass
soil 3rd rate
I carefully examined the adjustments of my solar compass to-day, particularly the latitude and reversing apparatus, and found them correct. Sept 17th 1884