

Chains.

North, between Sections 33 and 34.

Variation  $17^{\circ}40'$  East.Ascend  $8^{\circ}$  slope along  $\swarrow$  W. slope of ridge

40.00

Set a post 3 ft. long, 3 ins. diam. with marked stone 12 ins. in the ground, for  $\frac{1}{4}$  Sec. Cor., marked  $\frac{1}{4}$  S. on W. face, dug pits, 18 x 18 x 12 ins., N and  $\swarrow$  of post  $5\frac{1}{2}$  ft. dist., and raised a mound of earth  $1\frac{1}{2}$  ft. high,  $3\frac{1}{2}$  ft. base, around post.

44.00

Ascend  $12^{\circ}$  slope

61.00

Top of Ridge, bears NW and descend  $9^{\circ}$  slope

80.00

Set a limestone stone 18 x 9 x 9 ins. 12 ins. in the ground for Cor. to Secs. 27, 28, 33 & 34 marked with / notch on S. and 3 notch  $\llcorner$  on E. edges and dug pits, 18 x 18 x 12 ins. in each Sec.,  $5\frac{1}{2}$  ft. dist., and raised a mound of earth 2 ft. high,  $4\frac{1}{2}$  ft. base alongside

The necessary corrections corresponding to the giving slope  $\&$  has been applied and the corner  $\&$  located according to the true distance thus obtained.

Land mountainous  
sagebrush and bunchgrass  
soil  $\swarrow$  rate