

Chains

North, on a random line between Sections 4 and 5.

Variation

17'

East.

40.00

Set temporary $\frac{1}{2}$ sec. cor.

7987

Intersect N. B. of Tp. 27: 1ks E of cor. to secs

4, 5, 32 & 33.

which is a stone $14 \times 10 \times 10$ ins.marked with 4 notches on E and 2 notches on W edges
and mound of stone along sidefrom which cor. 1 run $S. 0^{\circ} 12' E$ on a true line between sections 4 & 5 with same va
Descend 5° slope along W slope of ridge

3987

Set a post 3 ft. long, 3 ins. diam. with marked stone
12 ins. in the ground, for $\frac{1}{2}$ Sec. Cor., marked $\frac{1}{2}$ S. on
W face, dug pits, $18 \times 18 \times 12$ ins. N and O of
post $5\frac{1}{2}$ ft. dist., and raised a mound of earth $1\frac{1}{2}$ ft.
high, $3\frac{1}{2}$ ft. base, around post.

6900

Dry Channel 26 1ks. wide, course S E.

7000

Enter nearly level land 600 E & W

7987

The cor. to secs. 4 - 5 - 8 & 9

The necessary corrections corresponding
to the giving slope has been applied and
the corner located according to the true
distance thus obtained.Rem. ~~scattering timber~~

sagebrush and bunchgrass

soil $3\frac{1}{2}$ rateAugust 31st - 1884