2-78

Township 20 NORTH Range 56 EAST

Monte Diablo Base and Meridian.

Chains.	North, on a true line between Sections 3 and 4. Variation 16°40' East.
	Over nearly level ground
8,00	Dry Channel 10 lks. wide, course West
34,40	Stream 3 lks. wide, runs S.W.
40,00	Set a post 3 ft. long, 3 ins. diam. with marked stone 12 ins. in the ground, for ¼ Sec. Cor., marked ¼ S. on W face, dug pits, 18 x 18 x 12 ins., N and S of post 5½ ft. dist., and raised a mound of earth 1½ ft. high, 3½ ft. base, around post.
41,00	Ascend 6° slope through scattering timber
56,00	Ascend 5° slope
79,86	Intersect the Fourth Standard Parallel North at a point 3,21 chs. West of the Standard Cor. to Secs. 33 and 34 T.21N R.56E which is a stone 19 x 13 x 18 ins. marked S C with 3 notches on E and 3 notches on W edges and mound of stone alongside
	at point of intersection 2
	Set a Prop stone 18 x 12 x 10 ins. 12 ins. in the ground for Closing Cor. to Secs. 3 and 4 marked C C. with 3 notches on E 3 notches on W. edges, and raised a mound of stone alongside. Pits impracticable.
	The necessary corrections corresponding to the giving slope A has been applied and the corner A located according to the true distance thus obtained.
	S 41 chs Land rolling sage and grass soil 2nd rate
	N 38.88 chs Land mountainous scattering timber soil 3rd " rate

September 27th 1884