308

Township 16 NORTH Range 57 EAST

Monte Diablo Base and Meridian.

Chains.

From the Standard Cor. to Secs. 35 & 36 Which is a post - 4 ins square Marked. S.C. T16N on N R57E S36 on E. S35 on W. Faces with 1 notch on E & 5 notches on W. Edges & pits N.E.&W of post 6 ft dist & Mound of Earth around post. Thence I run North between Secs 35 & 36 Variation 16°40' East.

Descend 4° slope

8.80 Ravine about 30 feet deep, course S E and ascend 6° slope

21.00 Top of Ridge, bears S E and descend 6° slope

38.00 Ravine about 60 feet deep, course S E and ascend 10° slope

40.00 Set a Stone stone 17 x 10 x 3 ins. 11 ins. in the ground, for ¼ Sec. Cor., marked ¼ on W face, and raised a mound of stone alongside. Pits impracticable.

45.80 Top of Ridge, bears S E and descend 8° slope

57.10 Stream 3 lks. wide, runs S E in ravine and ascend 10° slope

68.00 Ascend 6° slope

76.00 Top of Spur bears S E and ascend 4° slope

80.00 Set a Trap stone 20 x 18 x 10 ins. 15 ins. in the ground for Cor. to Secs. 25, 26, 35 & 36 marked with 1 notch on S. and 1 notch on E. edges and raised a mound of stone alongside. Pits impracticable.

The necessary corrections corresponding to the giving slope & has been applied and the corner & located according to the true distance thus obtained.

Land mountainous
scattering timber
soil 5th rate