

39 Ninth Standard Parallel North  
Township <sup>14<sup>7</sup></sup> Through Range 5 East  
Monte Diablo Base and Meridian.

West on S. boundary Sec. 9/

Variation  $18^{\circ}$  East.

Over nearly level ground

23.00 Descend <sup>clifftop</sup>  $12^{\circ}$  ~~bluff~~

31.00 Ravine about 6 feet deep, course N

and ascend gradually.

40.00 Set a post  $3\frac{1}{2}$  ft. long, 3 ins. diam. 12 ins. in the ground, for Standard & Sec. Cor., marked S. C.  $\frac{1}{4}$  on N. face, dug pits  $18 \times 18 \times 12$  E and W. of post  $5\frac{1}{2}$  ft. dist., and raised a mound of earth  $1\frac{1}{2}$  ft. high,  $3\frac{1}{2}$  ft. base around post.

62.00 head of Ravine - N.

80.00 Set a post  $4\frac{1}{2}$  ft. long, 4 ins. square, 12 ins. in the ground for Standard cor. to T 46 N on N marked S C., T 46 N on N R 25 E S. 31 on E and R 24 E S 36 on W faces with 6 notches on E. W. and N. notch on faces, dug pits  $18 \times 18 \times 12$  ins. N.E. & W. of post, 6 ft. dist. and raised a mound of earth 2 ft. high,  $4\frac{1}{2}$  ft. base around post.

<sup>top</sup> The necessary corrections corresponding to the giring slope has been applied and the corner located according to the true distance thus obtained.

Elevated table land

sagebrush and bunchgrass

soil 3<sup>d</sup> rate