

Mid Standard Parallel North
 Township Through Range 49 East 29
 Monto Diablo Base and Meridian.

Chains

West on S. boundary Sec. 31.

Variation $17\frac{1}{4}^{\circ}$ East

Descend 8° slope

125- Cross Road, bears NE & SW

3.00 Dry Channel 10 lks. wide, course SW
 and ascend 9° slope

21.00 Top of spur bears S and descend 7° slope

40.00 Set a post $3\frac{1}{2}$ ft. long, 3 ins. diam. 12 ins. in the
 ground, for Standard $\frac{1}{2}$ Sec. Cor., marked S. C. $\frac{1}{2}$ on N.
 face, dug pits 18 x 18 x 12 E and W of post $5\frac{1}{2}$ ft.
 dist., and raised a mound of earth $1\frac{1}{2}$ ft. high, $3\frac{1}{2}$ ft.
 base around post.

72.30 Road in ravine bears NW

77.00 same road & ravine bears SW

80.00 Set a second stone $20 \times 14 \times 10$ ins. 19 ins. in the
 ground for Standard Cor. to Tps. 16 N., R. 48 and 49 E
 on S. C. with 6 notches on NE & SW faces, and
 raised a mound of stone alongside. Pits impracticable.

The necessary corrections corresponding
 to the given slope & has been applied and
 the corner A located according to the true
 distance thus obtained.

Land mountainous, scattering timber
 sagebrush and bunchgrass
 soil $\frac{3}{4}$ rate

@ A31st 1884