

8 West boundary of
Township 16 NORTH Range 52 EAST

Monte Diablo Base and Meridian.

North between sections 1 & 6

Variation 17° East.

Over nearly level ground

29.50 Cross Ravine Course W. and ascend 8° slope

35.00 Over nearly level ground

40.00 Set a *lime* stone $15 \times 9 \times 8$ ins. 10
ins. in the ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W
face, and raised a mound of stone alongside. Pits impracticable.

64.00 Cross Road, bears $N 50^{\circ} E$ & $70^{\circ} W$

71.00 Dry Channel 15 fks. wide, course West

80.00 Set a post, $4\frac{1}{2}$ ft. long, 4 ins. square 12 ins. in the
ground, for Cor. to Tps. 16 and 17 N. R's 51 and 52

E, marked T. 17 N. S. 31, on N. E. R. 52 E. S. 6,
on S. E. T. 16 N. S. 1 on S. W. and R 51 E. S. 36,
on N. W. faces, with 6 notches on each edge, and raised
a mound of stone $2\frac{1}{2}$ ft. high, $5\frac{1}{2}$ ft. base around post.

The necessary corrections corresponding
to the given slope has been applied and
the corner located according to the true
distance thus obtained.

Land level and slightly rolling
sage and grass scattering timber
soil $1\frac{1}{2}$ rate