

34/7

Township 17 NORTH Range 50 EAST

Monte Diablo Base and Meridian.

North between sections 1 & 6

Variation 17° East.

X Descend 12° slope

9.00 Ravine about 30 feet deep, course East and ascend 5° slope

21.00 Top of Ridge, bears East and descend 5° slope

28.00 Ravine about 40 feet deep, course East

28.00 Cross Road, bears E & W and
Ascend 14° slope

40.00 Set a Sine stone $8 \times 10 \times 8$ ins. 11
ins. in the ground, for $\frac{1}{2}$ Sec. Cor., marked $\frac{1}{2}$ on W
face, and raised a mound of stone alongside. Pits impracticable.

41.00 Top of spur beam E along East slope of ridge

70.00 Descend 20° slope

80.00 Set a Sine stone $21 \times 14 \times 10$ ins. 10 ins. in
the ground for Cor. to Tps. 17 and 18 N R's 49 and 50
E marked with 6 notches on each edge, and raised a
mound of stone alongside. Pits impracticable.

The necessary corrections corresponding
to the given slope A has been applied and
the corner A located according to the true
distance thus obtained.

Land mountainous

Nut Pine and Cedar timber

soil $\frac{3}{10}$ rate

I carefully examined the adjustments of my solar com-
pass to-day, particularly the latitude and reversing
apparatus, and found them correct.

Nov 16th 1884