

Township 36 NORTH

Range 48 EAST

Monte Diablo Base and

Meridian.

Chains

From the corner to Sections 35, 36, ~~and 20~~ the South boundary, 1 ^{1/2} m.

which is a stone 18 x 13 x 9 ins.
marked with 5 notches on W and 1 notch on E sides
and mound of earth with pile Iron

North between sections 35 & 36
To 17° 40' East.

Ascend 4 of slope

40.00

Set a post 3 ft. long, 3 ins. diam. with marked stone
12 ins. in the ground, for 1/4 Sec. Cor., marked 1/4 S on
W face, dug pits, 18 x 18 x 12 ins., N and S of
post 5 1/2 ft. dist., and raised a mound of earth 1 1/2 ft.
high, 3 1/2 ft. base, around post.

80.00

Set a lime stone 14 x 10 x 9 ins. 9 ins. in
the ground for Cor. to Secs. 25, 26, 35 & 36 marked
with 1 notch on S. and 1 notch on E. edges and
dug pits, 18 x 18 x 12 ins. in each Sec., 5 1/2 ft. dist.,
and raised a mound of earth 2 ft. high, 4 1/2 ft. base
alongside

The necessary corrections corresponding
to the giving slope α has been applied and
the corner Δ located according to the true
distance thus obtained.

Land rolling

sagebrush and bunchgrass

soil $\text{S} \text{ (R) }_1$ rate