

Township 36 NORTH Range 48 EAST

Monte Diablo Base and Meridian.

Chains

From the cor. To Secs 2, 3, 34 & 35 on S. corner
which is a stone 16 x 9 x 7 ins.

marked with 4 notches on N. and 2 notches on E. edges
and mound of earth with pits. Iron
North between sections 34 and 35

Descend 3° Variation $17^{\circ} 45'$ East.

40.00

Set a *Siine* stone 13 x 9 x 8 ins. 10
ins. in the ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N
face, and raised a mound of stone alongside. Pits impracticable

42.00

Descend 5° slope

07.00

Ravine about 20 feet deep, course NW

Ascend 5° slope

78.00

Top of spur bears NW and descend 5° slope

80.00

Set a *Siine* stone 15 x 9 x 9 ins. 10 ins. in
the ground for Cor. to Secs. 26, 27, 34 & 35 marked
with 1 notch on S. and 2 notches on E. edges and
raised a mound of stone alongside. Pits impracticable.

The necessary corrections corresponding
to the giving slope Q has been applied and
the corner Q located according to the true
distance thus obtained.

Land rolling
sagebrush and bunchgrass
soil 2^{nd} rate