

Township 30 NORTH Range 48 EAST

Monte Diablo Base and Meridian.

Chains.

From the Established Cor. to Secs
23. 24. 25. 26

which is a stone $16 \times 9 \times 7$ ins.

marked with 2 notches on S and 1 notch on E edges
and mound of stone

Iron

North between sections 23 & 24.

Variation $17^{\circ} 40'$ East

Ascend 3° slope

40.00

Set a post 3 ft. long, 3 ins. diam. with marked stone
12 ins. in the ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ S. on
W face, dug pits, $18 \times 18 \times 12$ ins., N and S of
post $5\frac{1}{2}$ ft. dist., and raised a mound of earth $1\frac{1}{2}$ ft.
high, $3\frac{1}{2}$ ft. base, around post.

80.00

Set a lime stone $16 \times 10 \times 8$ ins. 11 ins. in
the ground for Cor. to Secs. 13. 14. 23 & 24 marked
with 3 notches on S. and 1 notch on E. edges and
dug pits, $18 \times 18 \times 12$ ins. in each Sec., $5\frac{1}{2}$ ft. dist.,
and raised a mound of earth 2 ft. high, $4\frac{1}{2}$ ft. base
alongside

The necessary corrections corresponding
to the giving slope has been applied and
the corner located according to the true
distance thus obtained.

Land rolling

sagebrush and bunchgrass

soil $\left(\frac{no}{11}\right)$ rate