

Chains.	North, on a random line between Sections 1 and 2.	
		Variation 17°40' East.

40.00 Set temporary 1/2 sec. cor.

79.90 Intersect North B. of Twp. 22 lks E of cor. to secs
 1, 2, 3, 5, 7, 8
 which is a stone 19 x 11 x 10 ins.
 marked with 3 notches on Wand / north ~~on~~ E edges
 and mound of stone
 from which cor. 1 run 79' E
 on a true line between sections 1 & 2 with some va
 Ascend 3° slope

18.00 Top of Ridge, bears E and descend 7° slope

37.00 Ravine about 7 feet deep, course East and
 Ascend 3° slope

39.90 Set a lime stone 15 x 9 x 5 ins. 10
 ins. in the ground for 1/2 Sec. Cor., marked 1/2 on W
 face, and raised a mound of stone alongside. Pits impracticable

42.00 Top of spur bears E. and
 Descend 6° slope

49.00 Ravine about 7 feet deep, course N.E. and
 Ascend 7° slope

79.90 The cor. to secs. 1, 2, 11, 8, 12

The necessary corrections corresponding
 to the giving slope 2 has been applied and
 the corner located according to the true
 distance thus obtained.

Land mountainous
 sagebrush and bunchgrass
 soil 8 ²⁰/₁₀₀ rate

March 13th 1886