

5th Standard Parallel North

Chs. Lying down, marked with Sh.
Ridge section, and faint
traces of old mound.

Where I set a lava rock $20 \times 18 \times 14$ ins. - 15 ins. in the ground
for reestablished Standard
Cor. To Sp. 41 N. Rs. $59 + 60$ E.
Marked 6 notches on N. E & W.
edges and S. C. dug pits $24 \times 18 \times 12$ ins. N. E & W. of stone $5\frac{1}{2}$
ft. dist. and raised a mound
of earth $1\frac{1}{2}$ ft. high 5 ft.
base along side.

I run.

West on S. side of Sec. 36.

4000 over dense sage brush $17^{\circ} 30'$ E.
Set lava rock $16 \times 12 \times 8$ ins. - 10 ins. in
the ground for Standard $1\frac{1}{2}$ Sec.
Cor. Marked $1\frac{1}{2}$ S. C. on N. face.
dug pits $18 \times 18 \times 12$ ins. E & W. of
stone $5\frac{1}{2}$ ft. dist. and raised a
mound of earth $1\frac{1}{2}$ ft. high $3\frac{1}{2}$
ft. base along side.

Good Ridge bras N. E. & S. W.

8000 Set lava rock $18 \times 14 \times 7$ ins. - 12 ins.