

## 3. Retracing

72

113.

Exterior F. 31 N. R. 44 E.

June 2<sup>nd</sup> 1893Begin at the S. W. corner of F. 31 N.  
R. 44 E. already described.

Thence I run

N. between Secs 31 &amp; 36.

Va. 17. E.

17.65

Road N.E.

33.50

Dry wash S.E.

4000

Set rock 18x10x8 ins. 12 ins. in ground  
for  $\frac{1}{4}$  Sec. cor. marked  $\frac{1}{4}$  on N. face  
Dug pit 2x2x2 ft.  $\frac{1}{4}$  Sec. 5  $\frac{1}{2}$  ft. dist  
and raised a mound of earth 2 ft. high  
by  $\frac{1}{4}$  ft. face alongside.From this point the old  $\frac{1}{4}$  Sec. cor. which  
is a stone lying loose upon the ground  
bears 10 links west.

I destroy the marking on this stone

64.00

Dry wash. S.E.

80.00

Set a post 4 ft. long 4 ins. square 24 ins  
in the ground for corner to sections 25  
30, 31 & 36 marked,

T. 31 N. S. 30 on N.E.

R. 44 E. S. 31 on S.E.

R. 43 E. S. 36 on S.W. and

S. 25 on N. W. faces, with 5 notches