

Submission of T. 38 N. R. 55 E.

- Corr random bet Secs. 25 & 36
- 4000 Set temp. 4 sec. cor.
- 8087 Intersect Ruby Valley Guide Meridian 1 ch. 66 lks S. of cor to Secs. 25, 30, 31 & 36 which is a rock family set & properly marked witnesses agreeing with Surveyor General's field notes. I re-build mound to the east. At the point of intersection set a granite rock 14x10x9 ins. 9 ins. in the ground for cor to Secs. 25 & 36 marked with 1 notch on S and 5 on N edges and raise a mound of stone 3 1/2 ft. base 2 1/2 ft. high W of cor. Then cor run W on this line bet Secs. 25 & 36.
- 1900 ^{in mangle} Ridge N. & S.
- 4019 Set a redwood post 3 ft. long 3 ins. sq. with marked stones 2 ft. in the ground for 4 sec. cor. nailed W. S. on N face deep pits 18x18 N 1/2 W. 2 ft. dist and raised a mound of earth 3 1/2 ft. base 2 1/2 ft. high N. of cor.
- 6000 Creek N.
0045 coal mine Road S.
8037 Cor to Secs. 25, 26, 35 & 36.
Land mountainous
Soil 3rd rate. Sagebrush & bunchgrass.