

Subdivision of T. 44 N. R. 55 E.

Chains	Cor. of sec. 1, 2, 11 and 12. North on a true line bet. sec. 1 and 2.
8.80	Road, bears N. W. and S. E.
9.00	Fence, bears N. W. and S. E.
13.00	Road, bears N. and S. along top of ridge
19.00	Leave road, bears N. W. and S. E.
39.20	Road, bears N. E. and S. W.
40.00	Set a quartzite stone 18 X 12 X 6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W. face, dig pits 18 X 18 X 12 ins. N. and S. ^{at 3 ft. dist.} and raise mound of earth 3 ft. base, 1 1/2 ft. high, W. of cor.
42.30	Road, bears N. W. and S. E.
64.65	Brush and laurel.
69.00	Road, bears N. W. and S. E.
72.00	Road, bears N. E. and S. W.
79.50	Road, bears N. E. and S. W.
80.20	Intersect N. body of Tp. 13. 87 ch. E. of 1/4 sec. cor. Set a sandstone 15 X 12 X 6 ins. 10 ins. in ground, for closing cor. of sec. 1 and 2 marked C.C. on S. face, with 1 groove on E and 5 grooves