

Subdivisions of T. 45 N. R. 55 E.

Chains

At cor. of secs 35 and 36 July 24, 1902 at 8^h 00^m A.M. L.M.T. I set off 19° 58' on decl. arc. 41° 45' N. on Cst. arc. and by the solar determine a true merid. Variation of magnetic north 18° 37' E., mean mag. decl. of needle as calculated by table page 100 in the manual of Surveys is 18° 31' E.

Thence, I run,

N 0° 1' W. bet. Secs. 35 and 36.

- 8.00 Draw course N.E. and ascend,
 32.00 Rocky ridge bears S.E. and N.W. descend
 40.00 Set a quartzite stone 14x10x8 ins. 9 ins. in ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face; dug pits 18x18x12 ins. N and S. of stone $\frac{3}{4}$ ft. dist and raised a mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.
 65.00 Road bears N.E. and S.W.
 68.00 S.W. End of Gold Creek Mining Cos. reservoir.
 71.00 Road on top of dam.
 80.00 Set a quartzite stone 14x8x7 ins. 10 ins. in ground for cor. of secs. 25, 26, 35 and 36. marked with 1 notch on S and E. edges. Dug pits 18x18x12 ins. in each sec. $5\frac{1}{2}$ ft.